

Gasman

Personal Single Gas Monitor

Flammable, Oxygen and Toxic Gases

CO₂
H₂S
Cl₂
NH₃
O₃
CO
O₂
CH₄
SO₂
CO₂
H₂S



Gasman

With rugged impact resistant construction and compliance to IP65, Gasman offer a wide range of gases including six flammable calibration options.

Designed for use in the toughest environments Gasman gives an unbeatable combination of powerful loud and bright alarms with a stunningly compact and lightweight design.

Simple

- True one button operation
- Easy to read backlit display for gas diagnostics and operating status
- Clear calibration due warning

Alarms

- 95dBA audible alarm
- Striking twin red/blue visual alarm
- Internal vibrating alarm
- 2 levels of instantaneous alarm and TWA alarms for toxic versions

Robust

- Tough polycarbonate housing
- Full overmoulding giving high impact resistance
- Water and dust resistant to IP65

Flexible

- Flammable, toxic and oxygen sensor solutions
- Rechargeable and Li-ion battery versions available
- Extensive data and event logging
- Fully interchangeable intelligent sensor modules

Gasman

Gasman is a range of rugged, compact single gas personal monitors designed for use in the toughest environments.

Gases and Ranges

Required ranges and alarms may vary by country and application and these can be configured as required. Each gas channel can have two instantaneous alarm levels set. Toxic units also have Time Weighted Average (TWA) alarms.

Flammable gas calibration is available for methane, propane, butane, pentane, hydrogen and ethylene as standard.

Gasman is also available in a safe area CO₂ version offering 0-5% carbon dioxide measurement.

Typical ranges and alarms

| Gas | Range | Standard Alarm (UK) |
|-------------------|------------|---------------------|
| Flammable | 0-100% LEL | 20% LEL |
| Oxygen | 0-25% | 19/23% |
| Hydrogen sulphide | 0-100ppm | 5ppm |
| Carbon monoxide | 0-500ppm | 30ppm |
| Sulphur dioxide | 0-20ppm | 1ppm |
| Chlorine | 0-20ppm | 0.5ppm |
| Nitrogen dioxide | 0-20ppm | 1ppm |
| Ammonia | 0-100ppm | 25ppm |
| Ozone | 0-1ppm | 0.1ppm |
| Hydrogen | 0-1000ppm | N/A |
| Hydrogen cyanide | 0-25ppm | 5ppm |
| Hydrogen fluoride | 0-10ppm | 1ppm |
| Phosphine | 0-5ppm | 0.2ppm |
| Fluorine | 0-1ppm | 0.1ppm |
| Phosgene | 0-1ppm | 0.1ppm |
| Nitric oxide | 0-100ppm | 25ppm |
| Carbon dioxide | 0-5% | 0.5% |

Gas Test Kit

The Gas Test Kit provides a simple and convenient means of carrying out either a pre-use (bump) test or a calibration.



Charging Options

The Gasman can be supplied with:

- Single unit charger with UK, EU or US plug or in-line 110V/230V supply
- Comms charger with options as above including PC interface
- 5-way multicharger with universal power supply
- Vehicle lighter socket charger for in-vehicle charging



A HALMA COMPANY

UK: 2 Blacklands Way, Abingdon Business Park, Abingdon, OXON, OX14 1DY
+44 (0) 1235 557700 sales@crowcon.com

US: 21 Kenton Lands Road, Erlanger, Kentucky 41018-1845
+1 859 957 1039 salesusa@crowcon.com

NL: Vlambloem 129, 3068JG, Rotterdam
+31 10 421 1232 eu@crowcon.com

SG: Block 194 Pandan Loop, #06-20 Pantech Industrial Complex, Singapore, 128383
+65 6745 2936 sales@crowcon.com.sg

www.crowcon.com

P01019 GB Issue 6 May 10

Specification:

| | |
|--|---|
| Weight | Flammable 138g (4.87oz) Toxic 118g (4.16oz) Oxygen 129g (4.55oz) Carbon monoxide 139g (4.90oz) |
| Dimensions | 90 x 48 x 24mm (3.5 x 1.9 x 0.95 inches) H x W x D |
| Typical Response Times (T₉₀) | Flammable 20s, Toxic Gas 20s, Oxygen 10s |
| Audible Alarms | 95dB Multiple alarm sounds allow selection of distinctive tones for different alarm levels. |
| Visible Alarms | Dual colour red/blue flashing LEDs in gas hazard |
| Vibrating Alarm | Internal vibrating alarm |
| Display | Custom LCD with backlight, with display of gas concentration. Graphic symbols for battery (with proportional indication of remaining operation time), and display mode. Start up indication when calibration is due within 30 days, calibration overdue or service required. |
| Display Modes | Normal display for real time gas concentration levels. Display recall for Peak readings and TWA. |
| Datalogging | Full timed datalogging with adjustable sample rate, set to 1 minute data rate as default. 900 hours storage at 1 min interval (54,000 logs), >4800 events |
| Battery | Rechargeable Li-ion battery for all gas types Non rechargeable Lithium battery for toxics and oxygen (excluding CO ₂) |
| Operating Time | Rechargeable: 12 hours minimum for flammable unit Non rechargeable: Up to 2 years Note: Operating time will depend on operating pattern and alarm occurrence. Frequent or long lasting alarms and use of the optional confidence beep will reduce battery life. |
| Sampling | Optional manual aspirator |
| Operating Temp. Range | -20°C to +65°C (-4°F to +149°F) Toxic and oxygen sensors are not rated for continuous operation at high temperatures. Consult Crowcon if operating temperatures are likely to exceed 40°C (104°F) for extended periods. |
| Humidity | 20-90% RH |
| Ingress Protection | IP65 |
| Approval Codes | <p><i>Europe</i></p> <p>Toxic/O₂: ATEX II 1G Ex ia IIC T4 Ga (-20°C ≤ Ta ≤ +65°C) BASEEFA04ATEX0384 Flammable: ATEX II 2G Ex ia d IIC T4 Gb (-20°C ≤ Ta ≤ +65°C) BASEEFA04ATEX0383</p> <p><i>International</i></p> <p>Toxic / O₂: IECEx BAS05.0039 Flammable: IECEx BAS05.0038</p> <p><i>N. America</i></p> <p>CSA Class 1 Groups A, B, C, D Division 1</p> |
| Standards Safety | <p><i>Europe</i></p> <p>EN60079-0, EN60079-11, EN60079-1, 94/9/EC</p> <p><i>N. America</i></p> <p>CSA22.2, 152</p> |
| Operation Standards | EN50270, EN50271, IEC61508, EN61779, EN45544 |
| PC Interface | RS232 connection from Interface module in charger RS232/USB converter available |
| Calibration | Gasman can be routinely calibrated using Portables PC software or by using Checkbox IMH |
| Accessories | Gasman is supplied with an integral alligator clip. |
| Optional Accessories | Hard hat harness, universal harness plate, shoulder strap, chest harness, leather case, aspirator assembly (flow plate, bulb and 2m/6ft tubing) and Gas Test Kit. |

Crowcon reserves the right to change the design or specification of the product without notice.

Area reserved for distributor stamp

CROWCON
Gas Detection You Can Trust