



Fixed systems for gas and fire monitoring

Gasmonitor Plus

Gasmonitor Plus

Gasmonitor Plus is our flexible microprocessor controlled system designed with a modular approach, so you get exactly what you want.

Used throughout the world, both on and offshore, Gasmonitor Plus provides the cost effective solution to your system requirements.

Gasmonitor Plus, the gas and fire control system you can trust.

Simple to use

Gasmonitor Plus offers flexibility whilst still providing simple operation. All the day to day functions are accessible via push buttons on the front panel.

As well as a rolling display, indicating the channel currently monitored, each channel has a bar graph display. This unique bar graph format is ranged to indicate readings below the first alarm setting, providing an instantaneous representation of the gas concentration on every detector.

Common alarm LEDs on the display card and individual alarms on the panel only light when a hazard or fault is detected. This means the whole rack status can be checked at a glance.

Flexible architecture

Each channel has three levels of alarm as well as a dedicated analogue output, set as 4-20 mA as standard.

Optional relay modules can interface to the panel to provide up to a total of 84 output relays per rack. Sixteen of these relays can be configured/voted from a combination of the three levels of alarm per channel.

The RS232 digital interface provides connectivity with PC for configuration, monitoring and datalog upload. Each rack is uniquely addressable, making multi-drop architectures possible. This cuts down on configuration and monitoring cabling.

Ground breaking design

Gasmonitor Plus is a microprocessor based expandable control system, which can be multiplied to offer unlimited channels and outputs.

Its modular construction provides ultimate customisation capacity with minimal wiring.

Gasmonitor Plus has industry standard analogue outputs, and the mechanical design is based on 19" Eurorack. This means that the Gasmonitor Plus will integrate fully with existing rack mounted protection systems on site.

The alochrome finish and rack screening plates ensure that the Gasmonitor Plus is impervious to radio frequency interference.

Easy maintenance

Gasmonitor Plus has been designed with easy servicing and maintenance in mind.

Each channel is inhibited separately so that plant safety is not compromised during maintenance checks.

Routine calibration can be achieved from the front panel. The one man calibration feature reduces the service overhead by half.

One universal gas card architecture controls all gas detectors. This reduces the spares holding required for Gasmonitor Plus maintenance. Each control card is fitted with its own dedicated micro-controller so it can function independently in the event of a single point failure.

Large, clear display

Individual channel
alarm inhibits

Channel alarm
indication



Unique
bargraph
reading per
channel

Common alarm indicators

Universal gas
input cards

Industry-standard
gas detectors

Remote reset switch

Dedicated external audio/
visual alarm drive

Up to 20 smoke/heat
detectors per zone



Optional
Battery
Backup




AC/DC
Power
Options

Analogue outputs per
channel
4-20mA or 1-5Vdc

Common and individual
channel relays for levels 1, 2,
3 and Fault

Optional voted relays



Gasmonitor Plus		
Size	483 x 133 x 294 mm (19.0 x 5.25 x 11.5 ins)	
Weight	9.5 kg (21 lbs)	
Enclosure material	Aluminium alloy	
Mounting	Rack mounted (3u format) ¹	
Channels	16 per rack	
Inputs	Gas	2 or 3 wire, 4-20 mA (sink or source), or mV bridge
	Fire - Smoke detectors, heat detectors and manual call points, up to 20 per loop	Maximum of 32 loops per rack (i.e. 16 twin zone fire modules)
Outputs	Analogue	16 x 4-20mA, max. load 960 Ohms or 1-5 V, min. load 100 Ohms
	External audio/visual alarm drive	Powered 24 V dc, max load up to 200mA for each alarm level
Relays	Type	Up to 84 DPCO contacts rated 5 A @ 250 V ac, non-inductive load
	Assignment	- common - per channel - voting
	Relay modes	Alarm 1, Alarm 2, Alarm 3, Fault Gas alarms 1, 2 & 3, fire & fault Up to 16, configurable energised, de-energised & latching, non-latching
Digital Communications	DCS/PLC/PC/Local configuration link	RS232
Logging	Built-in datalogger - data available via communication links	
Panel indication	Channel number Gas reading Measurement units System fault	4 lines x 20 characters back-lit LCD display as above plus green LED bar-graph ppm, %LEL, %vol, fire yellow LED
Alarm indication	Audible-internal sounder Visual	• 3 individual & 3 common alarms (red LED) individual & common fault (yellow LED) individual inhibit (yellow LED)
Power	AC mains DC Battery backup	100 - 260 V ac 50/60 Hz external 27.6 V dc, External
Remote Accept/Reset	•	
Lamp test	•	
Approvals	Low voltage directive RF immunity RF emissions	Meets BS EN 61010-1 Meets EN 50082-1 Meets EN 50081-1
Operating Temperature	0 to +50°C (32 to 122°F)	
Humidity	0 - 95% non-condensing	

1. Wall mounted and floor standing cabinets are optional, dimensions on request.

A HALMA COMPANY

P05003 Issue 7 05/07

UK Office
 Crowcon Detection Instruments Ltd
 2 Blacklands Way
 Abingdon Business Park
 Abingdon
 Oxfordshire OX14 1DY
 United Kingdom
 Tel: +44 (0) 1235 557700
 Fax: +44 (0) 1235 557749
 Email: sales@crowcon.com
 Web Site: www.crowcon.com

USA Office
 Crowcon Detection Instruments Ltd
 21 Kenton Lands Road
 Erlanger
 Kentucky 41018-1845
 USA
 Tel: +1 859 957 1039 or
 1-800-5-CROWCON
 Fax: +1 859 957 1044
 Email: salesusa@crowcon.com
 Web Site: www.crowcon.com

Rotterdam Office
 Crowcon Detection Instruments Ltd
 Vlambloem 129
 3068JG, Rotterdam
 Netherlands
 Tel: +31 10 421 1232
 Fax: +31 10 421 0542
 Email: eu@crowcon.com
 Web Site: www.crowcon.com

Singapore Office
 Crowcon Detection Instruments Ltd
 Block 194 Pandan Loop
 #06-20 Pantech Industrial Complex
 Singapore 128383
 Tel: +65 6745 2936
 Fax: +65 6745 0467
 Email: sales@crowcon.com.sg
 Web Site: www.crowcon.com

Crowcon reserves the right to change the design or specification of this product without notice